

**WHAT IS CLAIMED IS:**

1. A vacuum cleaner apparatus comprising:

at least one intake head;

5 at least one first cleaning element; and

at least one second cleaning element.

2. The apparatus of claim 1, wherein said at least one first cleaning element is a semi-absorbent pad.

10

3. The apparatus of claim 2, wherein said semi-absorbent pad is formed from ethylene propylene diene monomer foam.

15 4. The apparatus of claim 1, wherein said at least one first cleaning element comprises a supplemental wiping blade.

5. The apparatus of claim 1, wherein said at least  
20 one second cleaning element is a squeegee.

6. The apparatus of claim 5, wherein said squeegee comprises ridges.

7. The apparatus of claim 1, wherein said at least one second cleaning element is a brush.

5 8. The apparatus of claim 1, further comprising at least one third cleaning element.

9. The apparatus of claim 8, wherein said at least one third cleaning element are sidewalls.

10

10. The apparatus of claim 9, wherein said sidewalls are formed from ethylene propylene diene monomer foam.

11. The apparatus of claim 9, wherein said sidewalls  
15 do not extend beyond said at least one first cleaning element and said at least one second cleaning element.

12. The apparatus of claim 9, wherein said sidewalls contact said at least one first cleaning element and/or  
20 said at least one second cleaning element.

13. A vacuum cleaner apparatus comprising:  
at least one intake head;

at least one first cleaning element, wherein said  
at least one first cleaning element is a semi-absorbent  
pad;

at least one second cleaning element, wherein  
5 said at least one second cleaning element is a squeegee  
having ridges formed thereon.

14. A method of cleaning, comprising the steps of:

a) obtaining a vacuum cleaning attachment  
10 comprising at least one intake head, at least one first  
cleaning element, and at least one second cleaning element;

b) connecting said vacuum cleaning attachment to  
a vacuum source; and

c) moving said vacuum cleaning attachment over a  
15 surface to be cleaned.

15. The method of claim 14, further comprising the  
step of applying a cleaning solution to a surface to be  
cleaned.

20

16. The method of claim 14, wherein said at least one  
first cleaning element is a semi-absorbent pad.

17. The method of claim 16, wherein said semi-absorbent pad is formed from ethylene propylene diene monomer foam.

5 18. The method of claim 14, wherein said at least one second cleaning element is a squeegee.

19. The method of claim 18, wherein said squeegee comprises ridges.

10

20. The method of claim 14, wherein said at least one second cleaning element is a brush.

21. The method of claim 14, wherein said surface to  
15 be cleaned is the exterior of an automobile.